

PSNE300 Just Infusion, Syringe pump



Infuses only!

Just the features you want and none that you don't want to pay for.

Features:

- Holds big or small syringes up to 60 mL
- Pumps continuously until you stop the pump
- Change infusion rate while pumping
- Remembers previous settings on power up
- Syringe purge mode
- Power failure mode – continue pumping after reset
- Displays total volume dispensed in mL or μL
- Precise, reproducible flow rates
- Selectable infusion rates: mL/hr, $\mu\text{L/hr}$, mL/min, $\mu\text{L/min}$
- Infusion Rates: 0.73 $\mu\text{L/hr}$ (1 mL syringe) to 1,500 mL/hr (60 mL syringe)

Cost effective, easy to use, fully programmable fluid handlers
Visit our website for our full range of syringe pumps and accessories

www.syringepump.nl

Specifications

Mechanical & electrical

Syringe sizes:	Up to 140 cc
Number of syringes:	1
Motor type:	Step motor
Motor steps per revolution:	400
Micro-stepping:	1/8 to 1/2 depending on motor speed
Advance per step:	0.2126 μ m to 0.8504 μ m depending on motor speed
Motor to drive screw ratio:	15/28
Drive screw pitch:	20 revolutions/inch
DC connector:	2.1 mm, center positive
Voltage at DC connector:	12V DC at full load
Amperage:	800 mA at full load
Power supply type:	Unregulated linear external wall adapter, country and power source specific
Power supply output rating:	12V DC @ 1000 mA
Dimensions:	22.86 cm x 14.605 cm x 11.43 cm
Weight:	1.63 kg

Operational

Maximum speed	3.7742 cm/min
Minimum speed	0.004205 cm/hr
Maximum pumping rate	1257 mL/hr with a B-D 60 mL syringe
Minimum pumping rate	0.73 μ L/hr with a B-D 1 mL syringe
Maximum force	45 lbs. at minimum speed, 18 lbs. at maximum speed
Syringe inside diameter range:	0.100 to 50.00 mm

Syringe manufacturer	Syringe (μ L)	Inside diameter (mm)	Maximum rate (μ L/hr)	Minimum rate (μ L/hr)
SGE (Gas tight)	5	0.343	209.2	0.004
	10	0.485	418.3	0.008
	25	0.728	942.5	0.018
	50	1.03	1886	0.036
	100	1.457	3775	0.071
Hamilton	0.5	0.103	18.86	0.001
	1	0.146	37.91	0.001
	2	0.206	75.47	0.002
	5	0.326	189	0.004

Cost effective, easy to use, fully programmable fluid handlers
 Visit our website for our full range of syringe pumps and accessories

www.syringepump.nl



Syringe manufacturer	Syringe (mL)	Inside diameter (mm)	Maximum rate (mL/hr)	Minimum rate (µL/hr)	Maximum rate (mL/min)
B-D	1	4.699	39.27	0.73	0.654
	3	8.585	131	2.434	2.184
	5	11.99	255.6	4.748	4.261
	10	14.43	370.3	6.876	6.172
	20	19.05	645.4	11.99	10.75
	30	21.59	829	15.4	13.81
	60	26.59	1257	23.35	20.95
HSW Norm-Ject	1	4.69	39.11	0.727	0.651
	3	9.65	165.6	3.076	2.76
	5	12.45	275.6	5.116	4.594
	10	15.9	449.6	8.349	7.493
	20	20.05	714.9	13.28	11.91
	30	22.9	932.6	17.32	15.54
	50	29.2	1516	28.16	25.27
Monoject	1	5.74	58.59	1.088	0.976
	3	8.941	142.1	2.64	2.369
	6	12.7	286.8	5.326	4.78
	12	15.72	439.4	8.161	7.324
	20	20.12	719.9	13.37	11.99
	35	23.52	983.8	18.27	16.39
	60	26.64	1262	23.44	21.03
	140	38	2568	47.69	42.8
Terumo	1	4.7	39.28	0.73	0.654
	3	8.95	142.4	2.646	2.374
	5	13	300.5	5.581	5.009
	10	15.8	443.9	8.244	7.399
	20	20.15	722.1	13.41	12.03
	30	23.1	949	17.63	15.81
	60	29.7	1568	29.13	26.14
Poulten & Graf (Glass)	1	6.7	79.83	1.483	1.33
	2	8.91	141.1	2.622	2.353
	3	9.06	145.9	2.711	2.433
	5	11.75	245.5	4.559	4.092
	10	14.67	382.7	7.107	6.379
	20	19.62	684.6	12.72	11.41
	30	22.69	915.6	17.01	15.26
	50	26.96	1292	24.01	21.54
Steel Syringes	1	9.538	161.7	3.005	2.696
	3	9.538	161.7	3.005	2.696
	5	12.7	286.8	5.326	4.78
	8	9.538	161.7	3.005	2.696
	20	19.13	650.8	12.09	10.84
	50	28.6	1454	27.01	24.24
SGE (Gas tight)	0.25	2.303	9.432	0.176	0.157
	0.5	3.257	18.86	0.351	0.314
	1	4.606	37.73	0.701	0.629
	2.5	7.284	94.36	1.752	1.573
	5	10.3	188.6	3.504	3.143
	10	14.57	377.5	7.01	6.292
	25	23.03	943.2	17.52	15.72
	50	27.5	1344	24.98	22.4
	100	34.99	2177	40.43	36.28

Cost effective, easy to use, fully programmable fluid handlers
Visit our website for our full range of syringe pumps and accessories

www.syringepump.nl